

Preferred Pack[®]

MAILWRAPPER-280 • MAGAZINE PACKAGING MACHINE

Uses SW Polyethylene sheeting or SW Polyolefin Shrink Film



**Shown with Optional Powered Discharge Conveyor.*

The Mailwrapper-280 is the low cost alternative to high speed magazine poly bagging. Great for magazines, periodicals, instruction booklets or loose sheets of paper. An operator simply inserts one or several magazines up to 3/4" thick into the adjustable forming plow. The poly film is automatically wrapped around the product and is discharged into catch tray or optional powered discharge conveyor. For higher speed magazine wrapper ask about the CM-20P high speed polywrapper for cycle speeds of up to 120 ppm.

SEQUENCE OF OPERATION:



Film roll sets on powered film unwind rollers and feeds toward front of machine. Uses single wound polyethylene sheeting, plain or random printed. Maximum film thickness 2 mill. Meets USPS regulations, if using postal approved polyethylene.

If you have an application that requires using shrink film we recommend, the Quick Shrink Brand of polyolefin films sold exclusively through the Preferred Packaging Network of Dealers. It's quick seal time and low shrink temperature make this an ideal film.



Poly film feeds through adjustable forming shoe. Operator simply places magazine into forming shoe and releases. Product will automatically drop into sealing area where photo eye registers magazine length for cut off and automatic product ejection into a catch tray or optional power conveyor.



Convenient magazine catch tray will accumulate product.



Adjustable forming shoe with vertical and horizontal sealing bars. 1/2" thick shoe provided. Optional 3/4 " thick shoe available.



Easy to use and understand control panel.

| MODEL | POWER | SHIPPING WEIGHT | PRODUCTION RATE | MACHINE DIMENSIONS | BAG SIZE | MAX ROLL WIDTH |
|-----------------|--------------------|-----------------|-----------------|--------------------------|--|----------------|
| MAILWRAPPER 280 | 110 VOLT 10 AMP | 410 lbs. | 20-25 PPM | L W H 35" x 33" x 41" | MIN: 4"L x 6.5"W MAX: 17"L x 11.5"W | 24" |